HydroFIX casing pipe grab

Hydraulic pipe grab

OD 200 - OD 1500

with adapter for
EXCAVATORS



up to 7.5 t	OD 200 – OD 1500	140 bar	1,050 – 1,250 kg
Capacity	Pipe OD	Pressure rotate	Weight

OD to scale
○ max. ◌ min.
1 m

	EXCAVATOR AND WHEEL LOADER		EXCAVATOR		
Arm set	**OD 540 – OD 880**	**OD 600 – OD 1200**	**OD 200 – OD 1000**	**OD 200 – OD 1300**	**OD 200 – OD 1500**
Art. no.	**80982**	**80981**	**80977**	**80978**	**80979**
Capacity	3.0 t	5.5 t	5.5 t	5.5 t	7.5 t
OD min.	540 mm	600 mm	200 mm	200 mm	200 mm
OD max.	880 mm	1,200 mm	1,000 mm	1,300 mm	1,500 mm
Pressure open	200 bar	200 bar	200 bar	200 bar	200 bar
Pressure close	300 bar	300 bar	300 bar	300 bar	300 bar
Pressure rotate	140 bar	140 bar	–	140 bar	140 bar
Weight	1,050 kg	1,180 kg	1,070 kg	1,180 kg	1,250 kg

VERSIONS

ART. NO.	DESCRIPTION	WEIGHT
80982	HydroFIX casing pipe grab OD 540 - OD 880	1,050 kg
80981	HydroFIX casing pipe grab OD 600 - OD 1200	1,180 kg
80977	HydroFIX casing pipe grab OD 200 - OD 1000	1,070 kg
80978	HydroFIX casing pipe grab OD 200 - OD 1300	1,180 kg
80979	HydroFIX casing pipe grab OD 200 - OD 1500	1,250 kg
82015	Rotator	135 kg

EXCAVATOR ADAPTERS

ART. NO.	DESCRIPTION	WEIGHT
81601	OQ-80-S-42°	465 kg
81905	SW-66-S-42°	460 kg
81606	OQ-70/55-S-42°	320 kg
81915	SW-48-S-42°	350 kg

Compatible with attachment adapter, page 38

Schmölz SchachtFix & Baugeräte GmbH | Tel. +49 (0) 8349 9720 | vertrieb@schachtfix.info | schacht-fix.de

HydroFIX casing pipe grab

Hydraulic pipe grab

OD 540 - OD 1200

with adapter for
WHEEL LOADERS



FEATURES

- ✓ **Safe gripping of heavy casing pipes** with innovative Power Pad system and special rubber lining for maximum occupational safety
- ✓ **High load capacity up to 7.5 tonnes** for safe transport of even the heaviest casing pipes and cutting crowns
- ✓ Designed for **excavators and wheel loaders** – due to its weight, the large arm set OD 200 – OD 1500 works **exclusively** on excavators
- ✓ **Movable gripper plates adapt automatically to the pipe size –** adjustable to the millimetre from the excavator with a clear view
- ✓ **Hydraulic rotation with rotator** for millimetre-precise positioning and optimum manoeuvrability
- ✓ **Flexible pipe diameters OD 200 - OD 1500 with a clear scale** for quick adjustment to different pipe sizes
- ✓ **Robust design "Made in Germany"** for tough continuous use on large sites in specialist foundation engineering

VERSIONS

ART. NO.	DESCRIPTION	WEIGHT
80982	HydroFIX casing pipe grab OD 540 - OD 880	1,050 kg
80981	HydroFIX casing pipe grab OD 600 - OD 1200	1,180 kg
82015	Rotator	135 kg

WHEEL LOADER ADAPTERS

ART. NO.	DESCRIPTION	WEIGHT
82000	Wheel loader adapter L90 w/o LIKUFIX	440 kg
82001	Wheel loader adapter L90 with LIKUFIX	470 kg
82005	Wheel loader adapter L120 w/o LIKUFIX	
82006	Wheel loader adapter L120 with LIKUFIX	

Compatible with attachment adapter, page 38